

PHOENIX Operator Chair, black



Description

Lyreco exclusive state-of-the-art ergonomic manager operator chair featuring

- auto-synchro mechanism
- slim breathable fabric back with lumbar support
- high density cushioned sliding seat for comfort through long working hours
- height adjustable via gas lift
- adjustable 3D arms

Recommended Usage:

8 hours per day

Recommended Maximum Weight:

110kg

Warranty: 5 years

Test Certificates

EN 1335

BS 7176 – medium hazard



Optional Accessories

For maximum comfort and ergonomics an optional, easy to fix (and remove) headrest is available.

Breathable mesh headrest:

18.799.897

Product Dimensions

Product Dimension (as illustrated - in cm)			
Overall Width [W]	63	\	
Arms Inner Width [W1]	47	\	
Seat Width [W3]	48	\	
Seat Height [H2] (min/max)	44-51	\	
Seat Depth [D1]	44-49	\	
Back Width [W2]	45,5	\	
Back Height [H1]	60	\	
Chair cushion Depth [D2]	44-49	\	
Arms Height [H3] from floor (min/max)	62.5-69.5	\	
Overall Depth [D]	58.5-63.5	\	
Overall Height [H] (min/max)	95.5-102.5	\	
			Overall Dimensions [D*W*H]
			D62.5-69.5*W*H95.5-102.5 CM



TECHNICAL SHEET

Materials & Components

Material Name	Material Type	Fire Retardancy
Covering Materials (BACK)	100% polyester fabric	BS7176 - medium hazard
Covering Materials (SEAT)	100% polyester fabric	BS7176 - medium hazard
Foam Density (BACK)	n/a	n/a
Foam Density (SEAT)	42kg/cbm	BS7176 - medium hazard

Components	Material Type	Comments
Arms	Polypropylene	3D Arms / Load capacity 99.77 kg - 900 Newton
Mechanism	Steel	Self Tension Sychro Mechanism with seatslide 12% aluminum alloy, 80% carbon steel, 8% plastic
GasLift	Steel	Class 3 gas lift 35% cold rolled steel, 35% carbon steel, 27% plastic, 3% Nitrogen
Base	Nylon	Nylon base
Castors	Polypropylene	60mm castors

Logistic Information

Logistic Information	
Selling Unit of Measure	EACH
Number per Products per Carton	1
Carton Size (in cm)	74*37*65
Net Weight (in kg)	17
Gross Weight (in kg)	22