









**Dimensions:**

|                  |              |
|------------------|--------------|
| Seat height:     | 42-54 cm     |
| Seat width:      | 46 cm        |
| Seat depth:      | 45 cm        |
| Backrest height: | 485cm        |
| Total height:    | 90-103 cm    |
| Weight:          | 13,0-15,0 kg |
| Units:           | 1/carton     |

|   |   |   |   |
|---|---|---|---|
|    | Seat height adjustable in various positions by Toplift                          |  | Decorative and solid black polyamide base with foot glides                                    |
|    | Backrest with integrated lumbar support, height adjustable in various positions |  | This product has the GS-sign of the Intertek Fuerth and complies to all security requirements |
|   | Special moulding seat with seat depth inclination                               | <b>Features</b>   | including high gas spring and foot ring   |
|  | Permanent-contact-mechanism, for adjusting the backrest inclination             |   |   |

G20

**Fabrics: (100% polypropylene)**  
G03 – G28

**Optional against surcharge:**  
Castors for carpet floors  
Ring armrest „E“, article code: 6999  
Ring armrest „H“, article code: 7010



**Max. user height:** 1,92 m  
**Max. user weight:** 110 kg  
**Max. using time/day:** 8 hours



Art. code: T100G..T (counter)