TECHNICAL SHEET

6.469.453

GLOSSY LAMINATING POUCH 2X125MIC 54 X 86mm



Description

Excellent gloss,high transparency laminating pouch
Good moisture barrier and chemical resistance
With its unique 3-layer extrusion coating technology,laminating pouch provides enhanced clarity and bond strength.

Application

Water, grease and dirt resistant for excellent document protection
STD gloss finish produces enhanced, rich colours for a bright, clear and high shine appearance

Logistic datas

Product: 100pcs / pack

Box: 100 packs (10000pcs)

Technical specifications

Material: PET ,PP,EVA

Size: 54*86mm

Thickness per side : 125mic

Instructions for use

Before use, please make sure your laminator is preheated to the recommended temperature (usually 100–130°C, depending on your machine model).
Insert the document or item smoothly into the laminating pouch, leaving a small margin around the edges.
Place the pouch with the sealed edge first into the feeding slot of the laminator.
The machine will automatically pull the pouch through. Wait until the laminated item comes out completely from the other side.
After laminating, place the item on a flat, clean surface to cool down.
For best results, avoid wrinkling, folding, or overfeeding multiple items at the same time.

Eco friendly gesture

With GRS certificate
Packing is fully recyclable

Lyreco Management · Rue du 19 mars 1962 · 59770 Marly · France
Adresse postale : 59318 Valenciennes · cedex 9 · France
SAS au capital de 10 500 000 € · RCS Valenciennes 421 304 312